

Trolley série MGT-C Voltada

Parâmetros técnicos

modelo	Capacidade (Ton)	Flange Largura (mm)	Tamanho (mm)							N.W. (kg)	Raio mínimo de curva (m)
			M	A	B	C	D	H	S		
MGT-C050	0.5	50-152	270	194	176	28	75	30	32	10	0.8
MGT-C050L		50-203	322							10.5	
MGT-C100	1	64-203	334	236	196	32	96	38	40	14.5	0.9
MGT-C100L		64-305	436							16	
MGT-C150	1.5	74-203	337	250	210	36	102	38	45	18	1
MGT-C150L		74-305	439							20	
MGT-C200	2	88-203	343	268	226	42	109	38	52	22	1
MGT-C200L		88-305	445							24	
MGT-C300	3	100-203	357	322	266	52	124	40	63	34	1.2
MGT-C300L		100-305	459							38	
MGT-C500	5	124-203	373	362	301	62	142	42	74	47	1.3
MGT-C500L		124-305	475							53	
MGT-C800	8	124-203	400	426	388	72	185	45	110	77	2
MGT-C800L		124-305	502							83	
MGT-C1000	10	136-203	460	442	396	72	190	45	110	88	2
MGT-C1000L		124-305	503							94	
MGT-C1500	15	136-203	498	555	498	95	236	65	135	163	3.5
MGT-C1500L		136-305	602							170	
MGT-C2000	20	136-203	501	555	498	95	233	58	135	165	3.5
MGT-C2000L		136-305	604							174	